

PILOT

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.

 PLATINUM




89 g



PILOPSI



PILOPSF















PILOCSP

- + EXCELLENT FIELD OF VISION**
- + PP/TPR TWIN-MATERIAL FRAME**
- +  PLATINUM[®] COATING (P)**
- + ADJUSTABLE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**

bollé
SAFETY

PILOT

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PILOT	 Ventilated	PILOPSI	2C-1.2  1 BT 9 KN €€	 EN166 3 4 9 BT €€	Anti-scratch/anti-fog ()
	 Ventilated	PILOPSF	5-3.1  1 BT 9 KN €€	 EN166 3 4 9 BT €€	Anti-scratch/anti-fog ()
	 Ventilated CSP	PILOCSP	5-1.4  1 BT 9 KN €€	 EN166 3 4 9 BT €€	Anti-scratch/anti-fog ()

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

9. Molten metal and hot solids.

Mechanical strength symbols:


B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

€€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.


3. Liquid droplets.

4. Large dust particles > 5 microns.

9. Molten metal and hot solids.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM coating that sustainably combats fogging.

PLATINUM

The new exclusive scratch and fog resistant coating K and N certified PLATINUM guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CONDITIONNEMENT ET GENCOD EAN13			
	PILOPSI	PILOPSF	PILOCSP
Individual plastic bag	3660740003524	3660740007898	3660740007904
5 safety goggles per inner box	3660740103521	3660740107895	3660740107901
80 safety goggles per outer pack	3660740203528	3660740207892	3660740207908

CHARACTERISTICS	
LENSES	PC - 2,1 mm - Curve 5,5
FRAME	PP + TPR
TEMPLES	Non applicable
STRAP	Nylon
FOAM	No
SPARE LENSES	No



10/01/2019

Europe Bollé Safety
34 rue de la soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY