SPHERE

An exceptional field of vision of 180°. The easy to rise headgear and brow guard are adjustable for both height and depth and the SPHERE adapts itself to any situation for any use.





H ULTRA ENVELOPING 20,5 CM X 39,4 CM X 0,18 CM

- **H** ADJUSTABLE HEADGEAR AND BROW GUARD
- **B** PC FLIP-UP FACE SHIELD



SPHERE

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|--------|---------------|------------|-----------------------|----------------------|----------|
| SPHERE | Polycarbonate | SPHERPI | 2C-1,2 🗁 1 AT 8 9 C € | 🗁 EN166 3 8 9 AT C 🤆 | - |
| | Polycarbonate | FASPHERPI | 2C-1.2 🗁 1 AT 8 9 C € | - | - |

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

- 8. Electrical short circuit arc
- 9. Molten metal and hot solids

Mechanical strength symbols:

- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s
- A. High energy impact, resists a 6 mm, 0.86 g ball at 190 m/s
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

CE European standard 🗁 Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- 8. Electrical short circuit arc
- 9. Molten metal and hot solids
- A. High energy impact, resists a 6 mm, 0.86 g ball at 190 m/s
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- C€ European standard ∑ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.


CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| CHARACTERISTICS | | | | |
|-----------------|----------------|--|--|--|
| LENSES | PC - 2.0 mm | | | |
| FRAME | РР | | | |
| TEMPLES | Non applicable | | | |
| STRAP | Non applicable | | | |
| FOAM | Non applicable | | | |
| SPARE LENSES | PI | | | |





Europe Bollé Safety 34 rue de la Soie 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél. : 00 44 (0)208 391 4700 Fax : 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk

oollé

 \in

01/10/2020

bolle-safety.com