



VertiKlean[®] MAX[™] mop head

Disposable VertiKlean foam mop head with maximum absorbency

Description

The VertiKlean MAX disposable mop head is used with existing VertiKlean hardware for wet cleaning walls and ceilings in sterile and non-sterile environments.

Featuring a single layer of hydrophilic foam for unmatched absorbency, the foam head is backed by a semi-rigid thermoformed plate that easily snaps onto existing VertiKlean frames and provides uniform contact pressure on mopped surfaces.

Features and Benefits

- Lightweight and easy to maneuver
- Laser-cut for clean sealed edges
- Disposable mop head eliminates cross-contamination
- Mop heads are available sterile per AAMI guidelines
- Compatible with a wide range of solutions

Applicability

The information presented here is applicable to the part numbers shown below, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

VKMX0100, VKMX0150 (sterile), VKMX0200, VKMX0250 (sterile), VKMX0300, VKMX0350 (sterile)

Technical Data

Mop head component materials (cleaning surface first)	Knitted polyester fabric / 100ppi hydrophilic urethane foam / knitted polyester fabric / APET thermoform backplate	
Construction	Multi-layer; flame bonded / inert hi-temp adhesive	
Dimensions; (cm)		
VKMX0100; VKMX0150 (sterile)	11.0 W x 21.4 L x 1.9 H	
VKMX0200; VKMX0250 (sterile)	11.0 W x 32.4 L x 1.9 H	
VKMX0300; VKMX0350 (sterile)	11.0 W x 39.4 L x 1.9 H	
Dimensions; (in)		
VKMX0100; VKMX0150 (sterile)	4.3 W x 8.4 L x 0.7 H	
VKMX0200; VKMX0250 (sterile)	4.3 W x 12.8 L x 0.7 H	
VKMX0300; VKMX0350 (sterile)	4.3 W x 15.5 L x 0.7 H	

Attribute; (units)	Value **	Test Method
Mop weight, dry; (g/m ²)	1197	N/A
Sorbency in water		
Dry capacity; (mL/m ²)	6728	N/A
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/m ²)	0.56	
In isopropanol; (g/m ²)	1.68	
Particles ≥ 0.5µm; (x10 ⁶ /m ²)	58.5	IEST-RP-CC004.2, Sec. 5.2
Fibers > 100µm; (x10 ³ /m ²)	31.9	IEST-RP-CC004.2, Sec. 5.2

** ND = None detected; levels are below detection limit of test equipment

Notes:

- 1) Data shown are typical values and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 3) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 03/24/08



P.O. Box 530
 Spartanburg, SC 29304 USA
 Phone: +1-864-503-8333
 Fax: +1-864-503-8444
 Toll free US, Canada, PR: 1-800-289-5762

Customer Service
 United States: 1-866-855-4682
 Europe/Asia: +1-864-699-8257
 e-mail: wipers@contecinc.com
 www.contecinc.com