

# B0710 Clean White Long Sleeve



## Unsupported PVC coating

### DESCRIPTION

- Fully coated
- Extended bonded sleeve, elasticated border
- Raised finish
- Non-powdered, "slip-on" treatment
- Anatomical shape
- Eyelet for ventilation and hanging
- Available in "Clean packed" version



### BENEFITS

- A thin, light glove with a "second skin" feel
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments
- Surface enables a secure grip on slippery objects
- Easy to put on and remove, lint-free, dust-free
- Easy hang storage
- Designed for easy movement and continuous wear
- Extended protection for the entire arm

### RECOMMENDED FOR THESE RISKS:

Cold  
Chemicals

### RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Alkaline components  
Petrochemistry

### AVAILABLE SIZES

7/S • 8/M • 9/L • 10/XL

### LENGTH

Dependent on size, in mm (flat)

600

### PACKAGING

Pairs per pack/box

10/100, 5/100 (CP)

### COLOUR OF SUPPORT/COATING

White

### THICKNESS

in mm

0,30

### RECOMMENDATIONS FOR USE

- Do not use with chemicals other than those tested without prior trials
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work – other factors may influence the performance.
- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary



Globus Building  
38 Wheel Forge Way  
Trafford Park, Manchester  
M17 1EH

Tel: 0161 877 4747 Fax: 0161 877 4746



www.globus.co.uk

EC compliance certificate delivered by the notified body 0120 SGS Yarsley International Certification Services Ltd  
SGS House, 217-221 London Road Camberley, Surrey, GU15 3EY – United Kingdom

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



ABRASION CUTTING  
0 1 2 3 4 0 1 2 3 4 5  
TEARING PUNCTURE  
0 1 2 3 4 0 1 2 3 4



HYDROCHLORIC ACID 36% KEROSENE  
0 1 2 3 4 5 6 0 1 2 3 4 5 6

METHANOL CAUSTIC SODA 40%  
0 1 2 3 4 5 6 0 1 2 3 4 5 6

[ Updated 01/02/2010 ]

